

FIBERGLASS PIPING SYSTEMS

TS&M SUPPLY
FIBERGLASS

TS&M Supply is the distributor for Centron, Star, Bondstrand & Smith RT and GT fiberglass corrosion resistant products, including linepipe, downhole tubing, and low pressure facility piping products. Our many fiberglass piping options offer a number of benefits over traditional materials, like steel. Benefits of using fiberglass are ease of installation, reduced installation costs, elimination of failures due to corrosion, low maintenance and life cycle costs. With 35 years of experience selling Fiberglass products, TS&M's technical expertise, product selection and commitment to service and safety ensures we will meet your fiberglass requirements. TS&M field supervisors have solid industry experience and are qualified by the manufacturer to provide training certifications and supervision on the product and installation procedures; available 24 hours a day.



APPLICATIONS

- Flow / Emulsion lines
- Injection / Disposal lines
- Group lines
- Gas gathering & transport lines
- Low pressure battery & facility piping
- Acid / Polymer facilities
- Water processing
- De-watering lines
- Liners for linepipe & tubing
- Injection / Disposal tubing
- Production tubing
- Cement stingers
- Coal bed methane
- Casing
- CO₂, H₂S

FEATURES

- Corrosion resistant to commonly found corrosion elements in oil and gas applications (internal and external)
- Environmentally friendly option
- Can tie into any product: steel, spoolable, and fiberglass systems
- Supervision & technical services available
- Linepipe and downhole tubing operating pressures of up to 2500 PSI in sizes 2"-10"
- Prevents paraffin and scale build-up
- Flow characteristics 1½ times better than steel
- At ¼ the weight of steel, handling and installation costs are reduced substantially
- Fast, reliable, make-up; industry standard and premium end connectors available
- Can be assembled in any weather
- Tubing and casing with deep hole capabilities of more than 10,000 ft (3048 m)
- Temperature range up to 210°F (99°C)
- Facility piping operating pressures of up to 450 PSI in sizes 2"-16"



For more information on fiberglass products and services or for a customized solution, please contact your local TS&M representative or email tsm.fiberglass@dnw.com.